



Dry Powder Automatic Fire Extinguishers



Description

- Steel cylinder of high quality St 14 by means of deep drawing and painted with anti-corrosive polyester paint (powder coating).
- ABC dry chemical powder is effective on class A. B. C. & E fires and is ideal for multi-risk fires.
- Corrosion and impact resistant polyester paint finish.
- Operation with automatic sprinkler at temperature 68°C.
- Approved by Civil Defence and manufactured according to BS EN 3.
- Available in red color.

Specifications

DESCRIPTION	MODEL			
	FDPA4.5	FDPA5	FDPA6	FDPA12
CAPACITY(Kg)	4.5	5	6	12
FIRE RATING	21A 89B	21A 89B	21A 144B	21A 144B
DIAMETER(mm)	195	195	195	195
HEIGHT (mm)	400	400	410	500
DISCHARGE RANGE (Mtr)	8	8	8	9
DISCHARGE TIME (Sec)	12-14	12-14	16	21
CYLINDER WALL THICKNESS (mm)	1.8	1.8	1.8	2
CLASS OF FIRE	A B C & E			
EXTINGUISHING AGENT	ABC 70% DRY CHEMICAL POWDER			
OPERATING PRESSURE (Bar)	15			
TEST PRESSURE (Bar)	30			
OPERATING TEMPERATURE	68°C			
CYLINDER MATERIAL	COLD ROLLED STEEL			
PRINTING	CLEAR ATTRACTIVE SILK SCREEN PRINTING			
MOUNTING	CEILING MOUNTING			
EXPPELLANT AGENT	NITROGEN			



Wood, Rubber,
Paper, Textiles



Petrol, Oil, Greases,
other alcohol



Propane, Butane, methane,
Acetylene, Town gas



Fires on electrical
equipment.