



# Portable & Mobile Water Fire Extinguishers

## Description

- Water Fire Extinguishers are made of high quality steel ST14.
- Water Fire Extinguishers are effective on class A fire.
- Corrosive and impact resistant polyester paint finish (powder coating).
- All Extinguishers are coated internally for optimal protection against rust and corrosion.
- The valve is provided with safety release valve to release the excess pressure.
- These extinguishers are manufactured according to BSEN3 and approved by Local Civil Defence in U.A.E.
- Cylinders of different capacity can be supplied upon request.
- Water Fire Extinguishers are available in Red colour.

## Specifications of Portable Extinguishers

SPECIFICATION	MODEL			
	FW6L	FW9L	FW10L	FW12L
CAPACITY (Ltr)	6	9	10	12
DISCHARGE RANGE (m)	6	7	7	8
DISCHARGE TIME (sec)	≥9	≥9	≥9	≥12
TEST RATING	8A	13A	21A	27A
EMPTY WEIGHT (Kg)	2.5	3.55	3.55	3.98
GROSS WEIGHT (Kg)	8.5	12.55	13.55	15.98
OPERATING PRESSURE (Bar)	15			
TEST PRESSURE (Bar)	30			
EXTINGUISHING AGENT	WATER			
TEMPERATURE RANGE	+5°C TO +60°C			
CYLINDER MATERIAL	COLD ROLLED STEEL SHEET			
VALVE	BRASS, NICKLE PLATED WITH RIGID HANDLE & SAFETY VALVE PIN			
PAINTING	SUPERFINISHED ELECTRO PLASTIC POLYESTER EPOXY RESIN			
CARTON SIZE (m <sup>3</sup> )	0.014	0.024	0.024	0.03
CLASS OF FIRE	A			

## Specifications of Mobile Extinguishers

SPECIFICATION	MODEL				
	FW25L	FW50L	FW100L	FW125L	FW150L
CAPACITY (Ltrs)	25	50	100	125	150
DISCHARGE RANGE (m)	8	10	10	12	12
OPERATING PRESSURE (Bar)	15				
TEST PRESSURE (Bar)	30				
EXTINGUISHING AGENT	WATER				
TEMPERATURE RANGE	+5°C TO +60°C				
CYLINDER MATERIAL	COLD ROLLED STEEL SHEET				
VALVE	BRASS HOT STAMPING				
PAINTING	SUPER FINISHED ELECTRO-PLASTIC POLYESTER EPOXY RESIN				
CLASS OF FIRE	A				

